



RP35Si

Automatic Door Bottom Seal

TRADE PROFESSIONAL

Approvals:

certifire
CF 5710



Category J door bottoms are intended for application to/with Classified hollow metal and steel covered composite type fire doors rated up to and including 3 hrs. and wood and plastic covered composite and wood core fire doors rated up to and including 1-1/2 hrs.



Fire Rated:
FD240



200°C Smoke/Odours



70°C Smoke/Odours



Noise - Acoustic



Antimicrobial



Energy, Draughts and Dust



Insects and Vermin



Light



BAL - FZ (Flame Zone)



Access and Mobility



Medium Duty:
Tested to 1 million cycles



Length:

380mm

(Cuts back to 295mm)

820mm

(Cuts back to 600mm)

920mm

(Cuts back to 820mm)

1070mm

(Cuts back to 920mm)

Gap Size:

3 - 13mm

Colour:

Silver Anodised

Bronze Anodised

Exclusively brought to you by:



A: 1 Tampines North Drive 3 #07-09
BHCC Space
Singapore 528499
P: +65 6100 7824
E: support@faishak.com

A: G2, No. 5/16, Thayammal Kudil
Deva Raja St, West Tambaram
Tamil Nadu India 600045
P: +91 6369 1388 35
E: support@faishak.com